



- NOTES:
1. STONE SIZE ASTM D448 SIZE NO. 1, (1.5" - 3.5" DIA.)
 2. PAD THICKNESS 6" MIN.
 3. MIN. SIZE: 20'x50'.
 4. IF NECESSARY, INCLUDE WASHING
 5. MAY REQUIRE PERIODIC TOP DRESSING WITH 2" STONE.
 6. MAINTAIN IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOW OF MUD ONTO PUBLIC ROADS.
 7. PLACE STONE OVER FABRIC MATERIAL.
 8. USE RAIL WHEN THERE IS A POSSIBILITY OF HAZZARD DUE TO SLOPE.
 9. SEE ADDITIONAL EROSION CONTROL MEASURES IN THE EROSION CONTROL AND SEDIMENTATION ORDINANCE MANUAL AND THE GA. STATE EROSION CONTROL MANUAL.

FULTON COUNTY STANDARD DETAIL 402
CONSTRUCTION EXIT-TEMPORARY

DATE	REVISIONS	DATE	REVISIONS
8/08	NHR		

DGS/DRN/CHK: REB
APPROVED: _____
DATE: 12-2-05



FULTON COUNTY PUBLIC WORKS
141 PRYOR ST. ATLANTA, GA. 30303
404-612-7400 FAX: 404-224-0498

DRAWING NO.

402